



### POWER CABLE, C13 TO UK PLUG 3PIN, 100% COPPER, 18AWG, DESKTOP CABLE

**PART NO.:** PC-C13UK-xx

**DESCRIPTION:** Power Cable C13 to UK 3-Pin, 100% copper, 18AWG wiring

The KAYBE Power Cable (C13 to UK 3-Pin Plug) is designed to deliver safe and efficient power to desktop computers, monitors, and other electronic devices. Made with 100% copper and 18AWG wiring, it ensures excellent conductivity and reliable performance. Its durable construction and secure fit make it ideal for both home and office use.



#### KEY FEATURES

##### 1. Power Cord Connects Data Center Equipment to Reliable AC Power

This VDE-compliant power cable connects a PDU or UPS system with a C14 inlet to a BS 1363 wall outlet. It can also connect a computer, server, monitor or other device to a PDU, UPS or surge protector with BS 1363 outlets. Or you can extend an existing power connection up to one meter (3.3 feet). The P056-01M-UK features a BS 1363 end for connecting to an AC power source and an IEC-320-C13 end for connecting to a network device in a data center or other IT application.

##### 2. H05VV-F Jacket Is Fully VDE-Compatible for European Applications

The 0.75mm<sup>2</sup> enhanced PVC jacket complies with VDE, CE and UKCA standards for data centers, racks, workstations and other IT applications in Europe.

## SPECIFICATIONS

INPUT	
Maximum Input Amps	10
Voltage Compatibility (VAC)	250
CONNECTIONS	
Side A - Connector 1	BS1363 UK PLUG
Side B - Connector 1	IEC-320-C13
PHYSICAL	
Plug Color	Black
Cable Jacket Color	Black
Cable Jacket Material	PVC
Power Cord Jacket Type	H05VV-F
Cable Outer Diameter (OD)	6.7 mm
Number of Conductors	3
Conductor Gauge	24/0.20AS
Wire Gauge (AWG)	18
Wire Gauge (OD - mm <sup>2</sup> )	0.75
Power Cord Color	Black
Cable Length (ft.)	3.28
Cable Length (m)	1.00
Cable Length (cm)	100
ENVIRONMENTAL	
Operating Temperature Range	5° to 158° F (-15° to 70° C)
Storage Temperature Range	5° to 140° F (-15° to 60° C)
Operating Humidity Range	20% TO 80% RH, NON-CONDENSING
Storage Humidity Range	20% TO 80% RH, NON-CONDENSING
FEATURES & SPECIFICATIONS	
Antibacterial	No
Armored Cable	No
Angled Plug	No
High Voltage	Yes
Locking Plug	No
Coiled Power Cord	No
Locking	No
STANDARDS & COMPLIANCE	
Product Compliance	CE (Europe); REACH; RoHS; UKCA
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

## ORDERING INFORMATION AS PER FOLLOWS

PART NO	DESCRIPTION	LENGTH
PC-C13UK-1.8m	Power Cable (C13 to UK 3-Pin Plug)	1.8M
PC-C13UK-3m	Power Cable (C13 to UK 3-Pin Plug)	3M
PC-C13UK-5m	Power Cable (C13 to UK 3-Pin Plug)	5M

## OTHER PRODUCTS INCLUDE

DMX CABLES	SPEAKON SERIES	SDI CABLES	USB CABLES
POWER CABLE C5	POWER CABLE EXTENSION	CAT6A 10G PATCH VIDEO CABLE	CAT7 10G PATCH VIDEO CABLE